

## RoofEdge Premium



Product Properties		ARP100RM
Dims.	Edging height	100mm
	Edging length	2400mm
	Edging foot width	150mm
Other	Available finishes	Mill finish
	Material specification	Aluminium
	Recycling	100% recyclable

### Description

L-profile extruded aluminium edge restraint for heavy duty roof applications available in Rigid (RM) lengths in one height and thickness. Powder coat finishes available on request.

### Applications

To edge or demarcate roof surfacing materials, including those used in intensive green roof build-ups or brown roof installations on residential or commercial buildings. The holes on the vertical face of the edging provide a drainage path from the growing medium and drainage aggregate into gutters and outlets for any excess water, where retained green roof substrates require lateral drainage.

### Installation Information<sup>1</sup>

By installing the edge free-standing (weighed down by surface material) or bonding to membrane using a proprietary roofing adhesive (e.g. hot bitumen).

### Storage & Handling

The product is securely packed in a single flute cardboard carton to ensure no movement of the product in transit and each carton is sealed with a fibre tape. Depending on the size / weight of the consignment this may be palletised.

Whilst there is no specific weight restrictions on what is or is not safe to lift in manual handling, an assessment of the health and safety risks should be undertaken and measures taken to reduce the risk of injury so far as reasonably practicable.

The following guidelines may be useful:

- Each person should be fully trained in manual handling techniques.
- The use of handling aids such as a trolley, folk-lift, pallet truck or conveyor should be used if moving large volumes of cartons.
- Break up large consignments into more manageable loads.
- Ensure that the product is stored at a reasonable height, so avoiding the lifting of cartons from floor level or above shoulder height.
- Reduce carrying distances of cartons.

### Protective Equipment

We recommend that PPE (Personal Protective Equipment) is used when installing RoofEdge Premium:

- Good strong safety boots/shoes to protect the feet.
- Protective eyewear such as safety glasses.
- Strong gloves to protect the hands.
- If using loud cutting equipment then ear plugs or defenders should be worn.

### First Aid

The Health and Safety Regulations 1981 require all construction sites to have the following:

- A first aid box with enough equipment to cope with the number of workers on site.

### First Aid (continued)

b) An Appointed Person to take charge of first-aid arrangements. The Appointed Person looks after first aid equipment and facilities and calls the emergency services when required. Appointed Persons do not need first aid training.

c) A First-Aider who has undertaken training and holds an HSE approved qualification to administer first-aid. This means that they must hold a valid certificate of competence in either:

- First aid at work (FAW) issued by a training organisation approved by HSE
- Emergency first aid at work (EFAW) issued by a training organisation approved by HSE
- A recognised Awarding body of Ofqual/Scottish Qualifications Authority.

d) The number of first-aiders will depend on the site.

e) Information should be clearly displayed on site telling workers the name of the Appointed Person(s) or First Aider(s) and where to find them.

### Fire Protection

RoofEdge Premium is made using aluminium which does not burn and is not a fire hazard.

### Stability

All building materials are eventually degraded by weathering, corrosion, rot and decay. Aluminium's natural ability to resist these influences better than many materials is one of its most widely appreciated features. Aluminium reacts with the oxygen in the air to form an extremely thin layer of oxide; this layer is dense and provides excellent corrosion protection, and is self-repairing if damaged.

In its unprotected '*Mill Finish*' form aluminium is used very successfully for long-life everyday products making RoofEdge Premium exceptionally suitable for use as a commercial edging system.

### Environmental Issues

RoofEdge is 100% recyclable. As a result the whole life cost of aluminium edging is excellent as it is sold for recycling not paid disposal.

There are plenty of raw materials for the production of aluminium. In a variety of forms, aluminium compounds make up a full 8% of the Earth's crust. Bauxite is the main starting point in the production of aluminium and given current rates of production there is enough bauxite to last another 200 to 400 years, this based upon no increases in the use of recycled aluminium and no further discoveries of

bauxite. Furthermore the volume of aluminium being recycled is at a level where the requirement for virgin alumina is decreasing – further lessening the environmental impact.

### Supporting Documents

More information on the RoofEdge Premium product can be found at [www.kinley.co.uk](http://www.kinley.co.uk) in the Resource Centre. In particular, look for the CAD Drawings, Installation Guide (IG-ARP-0616) and Edging Book (BR-EB-0116).

1. The *Installation Information* given in this document is intended as a guide only. We recommend that professional opinions are obtained before work is commissioned. Kinley Systems Ltd accepts no responsibility for any damage or loss as a result of using the *Installation Information*. We will be happy to engage in any discussion with regard to specific project applications.